

**FEATURES:**

- Traditional Footprint
- Economical Cost Savings
- Surface Mount or Suspension
- Rugged, Steel Construction
- White Finish
- Pre-Wired Tombstone Sockets
- Multiple Knockout for Tandem Installations

APPLICATIONS:

- Task
- Warehouse
- Retail
- Gymsnasiums
- General Applications

***A BLANK CANVAS FILLED WITH
OPTIONS FOR MANY APPLICATIONS***

SATCO|NUVO's Dual T8 Lamp Ready Fixture Channels are the economical solution for upgrading traditional lighting to more efficient LED technology. These T8 Lamp Ready Fixture Channels are available in 2', 3' and 4' lengths and possess a traditional footprint, eliminating the need to make repairs or patch ceilings when retrofitting existing lighting. With their pre-wired tombstone sockets and multiple wiring knockouts located on the sides and back panels, new installations and retrofits will be effortless. A full suite of accessories are available including add-on reflectors, protective cages and a suspension mounting kit.

SATCO also offers a full line of recommended T8 LED lamps to compliment the fixture channels. Please view our expansive lamp guide by scanning our QR Code and select the lamps best suited for your installation application.



**SCAN TO VIEW THE
COMPLETE LAMP
WIRING GUIDE**



**SCAN TO VIEW THE
INSTALLATION &
SAFETY INSTRUCTIONS**

OPTIONAL ACCESSORIES



Cambered Protective Cage
Available in 2', 3' & 4'

** Cambered Protective Cages cannot be
attached without the Reflector*



3' Empty Body
Suspension Kit



Add-On Reflector
Available in 2', 3' & 4'

2', 3', and 4' Fixtures

Item	Description	Dimensions	Finish	UPC	Pack
65-910	2' Dual T8 Fixture Channel	L:24.45 W:4.65 H:3.01	White	045923659324	1
65-911	3' Dual T8 Fixture Channel	L:36.46 W:4.65 H:3.01	White	045923659331	1
65-912	4' Dual T8 Fixture Channel	L:48.46 W:4.65 H:3.01	White	045923659348	1

Accessories

Item	Description	UPC	Pack
65-913	2' Add-On Reflector	045923659355	1
65-914	3' Add-On Reflector	045923659362	1
65-915	4' Add-On Reflector	045923659386	1
65-916*	2' Cambered Protective Cage	045923659393	1
65-917*	3' Cambered Protective Cage	045923659409	1
65-918*	4' Cambered Protective Cage	045923659416	1
65-919	3' Empty Body Suspension Kit	045923659904	1

** Cambered Protective Cages cannot be attached without the Reflector*

SATCO DISTRIBUTION CENTERS

NEW YORK (HQ)

110 HEARTLAND BLVD
BRENTWOOD, NY 11717
T. 631-243-2022
F. 631-243-2027

TEXAS

2000 VALWOOD PKWY
FARMERS BRANCH, TX 75234
T. 972-247-2437
F. 972-247-5408

FLORIDA

1694 NW 215TH ST
MIAMI GARDENS, FL 33056
T. 305-624-2044
F. 305-623-0286

CALIFORNIA

31288 SAN BENITO ST
HAYWARD, CA 94544
T. 510-487-4822
F. 510-487-8955

WASHINGTON

4710 116TH ST SW
MUKILTEO, WA 98275
T. 425-789-3300
F. 425-789-3310

PUERTO RICO

CAMPECHE STREET, 23
JULIO N. MATOS INDUSTRIAL PARK
CAROLINA, PR 00984
T. 787-757-3510
F. 787-757-3540

For international sales, contact: internationalsales@satco.com / 631-243-2022 Ext. 315

LED Hybrid T8 Tube

Item	Description	Voltage	Watts	LM	M.O.L.	Life/Hrs	UPC
S8890	13T8/LED/48-830/DUAL/BP-DR	120-277V	13W	1800L	48	50K	045923088902
S8891	13T8/LED/48-835/DUAL/BP-DR	120-277V	13W	1800L	48	50K	045923088919
S8892	13T8/LED/48-840/DUAL/BP-DR	120-277V	13W	1900L	48	50K	045923088926
S8893	13T8/LED/48-850/DUAL/BP-DR	120-277V	13W	1900L	48	50K	045923088933



**SCAN TO VIEW THE
COMPLETE LAMP
WIRING GUIDE**

Flicker Free LED T8 Bypass

Item	Description	Voltage	Watts	LM	M.O.L.	Life/Hrs	UPC
S11910	11.5T8/LED/48-830/BP	120-277V	11.5W	1650L	48	50K	045923119101
S11911	11.5T8/LED/48-835/BP	120-277V	11.5W	1650L	48	50K	045923119118
S11912	11.5T8/LED/48-840/BP	120-277V	11.5W	1750L	48	50K	045923119125
S11913	11.5T8/LED/48-850/BP	120-277V	11.5W	1800L	48	50K	045923119132
S11914	18.5T8/LED/48-830/BP	120-277V	18.5W	2400L	48	50K	045923119149
S11915	18.5T8/LED/48-835/BP	120-277V	18.5W	2400L	48	50K	045923119156
S11916	18.5T8/LED/48-840/BP	120-277V	18.5W	2500L	48	50K	045923119163
S11917	18.5T8/LED/48-850/BP	120-277V	18.5W	2600L	48	50K	045923119170

CCT Selectable LED Linear T8 Type B Lamps

Item	Description	Voltage	Watts	LM	M.O.L.	Life/Hrs	UPC
S11919	12.5T8/LED/48/840-850-865/BP/2	120V-277V	12.5W	1800L	48	50K	045923119194
S11929	12.5T8/LED/48/840-850-865/BP	120V-277V	12.5W	1800L	48	50K	045923119293
S11969	12.5T8/LED/48/830-835-840/BP	120V-277V	12.5W	1700L/1750L/1800L	48	50K	045923119699

LED T8 4' type A/B Bypass & Direct Replacement

Item	Description	Voltage	Watts	LM	M.O.L.	Life/Hrs	UPC
S11974	12T8/LED/48-830/DM/A-B	120V-277V	12W	1700L	48	50000	045923119743
S11975	12T8/LED/48-835/DM/A-B	120V-277V	12W	1700L	48	50000	045923119750
S11976	12T8/LED/48-840/DM/A-B	120V-277V	12W	1800L	48	50000	045923119767
S11977	12T8/LED/48-850/DM/A-B	120V-277V	12W	1800L	48	50000	045923119774

LED T8/4' Double & Single Ended Bypass/Line Voltage

Item	Description	Voltage	Watts	LM	M.O.L.	Life/Hrs	UPC
S11960	10.5T8/LED/48-830/BP/SE-DE	120V-277V	10.5W	1700L	48	50000	045923119606
S11961	10.5T8/LED/48-835/BP/SE-DE	120V-277V	10.5W	1700L	48	50000	045923119613
S11962	10.5T8/LED/48-840/BP/SE-DE	120V-277V	10.5W	1700L	48	50000	045923119620
S11963	10.5T8/LED/48-850/BP/SE-DE	120V-277V	10.5W	1700L	48	50000	045923119637
S11988	10.5T8/LED/48-830/BP/USA	120V-277V	10.5W	1700L	48	50000	045923119880
S11989	10.5T8/LED/48-835/BP/USA	120V-277V	10.5W	1700L	48	50000	045923119897
S11990	10.5T8/LED/48-840/BP/USA	120V-277V	10.5W	1700L	48	50000	045923119903
S11991	10.5T8/LED/48-850/BP/USA	120V-277V	10.5W	1700L	48	50000	045923119910
S39913	14T8/LED/48-830/BP/SE-DE	120V-277V	14W	1700L	48	50000	045923399138
S39914	14T8/LED/48-835/BP/SE-DE	120V-277V	14W	1700L	48	50000	045923399145
S39915	14T8/LED/48-840/BP/SE-DE	120V-277V	14W	1800L	48	50000	045923399152
S39916	14T8/LED/48-850/BP/SE-DE	120V-277V	14W	1800L	48	50000	045923399169
S21924	14T8/LED/48-865/BP/SE-DE	120V-277V	14W	1800L	48	50000	045923219245
S11992	14T8/LED/48-830/BP/USA	120V-277V	14W	1700L	48	50000	045923119927
S11993	14T8/LED/48-835/BP/USA	120V-277V	14W	1700L	48	50000	045923119934
S11994	14T8/LED/48-840/BP/USA	120V-277V	14W	1800L	48	50000	045923119941
S11995	14T8/LED/48-850/BP/USA	120V-277V	14W	1800L	48	50000	045923119958
S39904	17T8/LED/48-830/BP/SE-DE	120V-277V	17W	2100L	48	50000	045923399046
S39905	17T8/LED/48-835/BP/SE-DE	120V-277V	17W	2100L	48	50000	045923399053
S39906	17T8/LED/48-840/BP/SE-DE	120V-277V	17W	2200L	48	50000	045923399060
S39907	17T8/LED/48-850/BP/SE-DE	120V-277V	17W	2200L	48	50000	045923399077
S11996	17T8/LED/48-830/BP/USA	120V-277V	17W	2100L	48	50000	045923119965
S11997	17T8/LED/48-835/BP/USA	120V-277V	17W	2100L	48	50000	045923119972
S11998	17T8/LED/48-840/BP/USA	120V-277V	17W	2200L	48	50000	045923119989
S11999	17T8/LED/48-850/BP/USA	120V-277V	17W	2200L	48	50000	045923119996



**SCAN TO VIEW THE
COMPLETE LAMP
WIRING GUIDE**

LED T8/2' Double & Single Ended Bypass/Line Voltage

Item	Description	Voltage	Watts	LM	M.O.L.	Life/Hrs	UPC
S11980	9T8/LED/24-830/BP/USA	120V-277V	9W	1100L	24	50000	045923119804
S11981	9T8/LED/24-835/BP/USA	120V-277V	9W	1100L	24	50000	045923119811
S11982	9T8/LED/24-840/BP/USA	120V-277V	9W	1150L	24	50000	045923119828
S11983	9T8/LED/24-850/BP/USA	120V-277V	9W	1150L	24	50000	045923119835
S39900	9T8/LED/24-830/BP/SE-DE	120V-277V	9W	1100L	24	50000	045923399008
S39901	9T8/LED/24-835/BP/SE-DE	120V-277V	9W	1100L	24	50000	045923399015
S39902	9T8/LED/24-840/BP/SE-DE	120V-277V	9W	1150L	24	50000	045923399022
S39903	9T8/LED/24-850/BP/SE-DE	120V-277V	9W	1150L	24	50000	045923399039



LED T8/3' Double & Single Ended Bypass/Line Voltage

Item	Description	Voltage	Watts	LM	M.O.L.	Life/Hrs	UPC
S11984	12T8/LED/36-830/BP/USA	120V-277V	12W	1400L	36	50000	045923119842
S11985	12T8/LED/36-835/BP/USA	120V-277V	12W	1400L	36	50000	045923119859
S11986	12T8/LED/36-840/BP/USA	120V-277V	12W	1450L	36	50000	045923119866
S11987	12T8/LED/36-850/BP/USA	120V-277V	12W	1450L	36	50000	045923119873
S39926	12T8/LED/36-830/BP/SE-DE	120V-277V	12W	1400L	36	50000	045923399268
S39927	12T8/LED/36-835/BP/SE-DE	120V-277V	12W	1400L	36	50000	045923399275
S39928	12T8/LED/36-840/BP/SE-DE	120V-277V	12W	1450L	36	50000	045923399282
S39929	12T8/LED/36-850/BP/SE-DE	120V-277V	12W	1450L	36	50000	045923399299



**SCAN TO VIEW THE
COMPLETE LAMP
WIRING GUIDE**

LED Type C Lamps

Item	Description	Voltage	Watts	LM	M.O.L.	Life/Hrs	UPC
S11930	8T8/LED/24-830/XD	120V-277V	8W	1200L	24	50000	045923119309
S11931	8T8/LED/24-835/XD	120V-277V	8W	1200L	24	50000	045923119316
S11932	8T8/LED/24-840/XD	120V-277V	8W	1200L	24	50000	045923119323
S11933	8T8/LED/24-850/XD	120V-277V	8W	1200L	24	50000	045923119330
S11934	11T8/LED/36-830/XD	120V-277V	11W	1600L	36	50000	045923119347
S11935	11T8/LED/36-835/XD	120V-277V	11W	1600L	36	50000	045923119354
S11936	11T8/LED/36-840/XD	120V-277V	11W	1600L	36	50000	045923119361
S11937	11T8/LED/36-850/XD	120V-277V	11W	1600L	36	50000	045923119378
S11938	12T8/LED/48-830/XD	120V-277V	12W	1800L	48	50000	045923119385
S11939	12T8/LED/48-835/XD	120V-277V	12W	1800L	48	50000	045923119392
S11940	12T8/LED/48-840/XD	120V-277V	12W	1800L	48	50000	045923119408
S11941	12T8/LED/48-850/XD	120V-277V	12W	1800L	48	50000	045923119415