Tester:	Jinglan Zeng			Date:		11/Sep/2023	
1	Item number			62/1747/EM			
2	Power source			2pcs IFR18650 2000mAh 3.2V			
3	Input frequency			NA			
4	Power supply properties			Emergency Power Supply			
5	Lux meter			EVERFINE Z-10			
6	Number of samples			1рс			
7	Voltage of full charged batteries without load			7.3V			
				Equipment Model	Illum	ninance Meter	
	3000K	%	***Lux 220cm		EVE	ERFINE Z-10	
Time(min)	Lux *200cm, **60cm	of Lux	Center			Remark	
Battery ON	21.5						
0	21.5	100.0%	90.6		Charge for 24 H, the green light is on, 100%		
15	21.1	98.1%	88.9				
20	19.5	90.7%	82.0		complete charge, collect the luminance value		
30	16.5	76.7%	69.3				
40	16.5	76.7%	69.1		corresponding to the		
50	13.3	61.9%	55.9		color temperature at different points in time.		
60	11.6	54.0%	49.0				
70	11.6	54.0%	48.9		*Light cone height 2	cone height 200cm	
80	10.0	46.5%	42.0		**Radius of the base of the light cone 30cm ***Center of the base of		
90	10.0	46.5%	42.0				
130	0.0	0.0%	0.0		the ligi		
130	Light off				J		
Tester: Jingian zeng Auditor: Jingian zeng Approved by: Snunyang Chen							
Trend:							

