Tester:	Jinglan Zeng			Date:		11/Sep/2023		
1	Item number			62/1756/EM				
2	Power source			3pcs IFR18650 2000mAh 3.2V				
3	Input frequency			NA				
4	Power supply properties			Emergency Power Supply				
5	Lux meter			EVERFINE Z-10				
6	Number of samples			1pc				
7	Voltage of full charged batteries without load			11.2V				
				Equipment Model	Illun	ninance Meter		
	3000K	%	***Lux	Lquipinent woder	EVE	ERFINE Z-10		
Time(min)	Lux *200cm, **60cm	of Lux	200cm Center			Remark		
Battery ON	37.8							
0	37.8	100.0%	123.6		Charge for 24 H, the			
15	37.4	98.9%	122.4		green light is on, 100% complete charge, collect the luminance value corresponding to the color temperature at different points in time.			
20	35.0	92.6%	112.2					
30	33.0	87.3%	107.7					
40	32.9	87.0%	107.5					
50	29.9	79.1%	97.6					
60	28.6	75.7%	93.5		unere	nii poiniis in time.		
70	28.7	75.9%	93.9		*Light cone height 20	cone height 200cm		
80	23.3	61.6%	76.2			us of the base of		
90	17.5	46.3%	57.2		the light cone 30cm ***Center of the base of			
124	0.0	0.0%	0.0		the light o	ht cone		
124	Light off							
Tester: Jingian zeng Auditor: Jingian zehg Approved by: Snunyang Chen								
Trend:								

