

- Spectrum Report (EVERFINE HAAS-1200)
- Photobiological Safety Report (IEC 62471)

1. Product Overview

The **EVERFINE HAAS-1200** are high color rendering LED lighting modules designed for professional and commercial environments. They are available in multiple color temperatures, offering versatility in lighting design, with a CRI (Color Rendering Index) of ≥ 92 , ensuring accurate and vibrant color reproduction.

2. UV Output and Photobiological Safety

According to the **EVERFINE HAAS-1200 Spectrum Test Report**, the **peak wavelength** is **355.4 nm**, which falls within the **UVA range (315–400nm)**.

The product emits a **very low level of UV radiation**, with no significant UVB or UVC detected, minimizing the risk of photochemical damage to artworks.

► IEC 62471 Safety Rating:

The product was tested under **IEC 62471** and classified as:

Exempt Group (No UV hazard)

Exempt Group means the product does not pose any photobiological hazard, including UV exposure, under typical operating conditions. This classification makes it safe for use in environments like **art galleries** and **museums**, where sensitive artworks are present.

3. Suitability for Artworks

Due to its **minimal UV output** and **high color fidelity**, the **EVERFINE HAAS-1200** are ideal for illuminating sensitive artworks, including:

- Oil, acrylic, and watercolor paintings
- Sculptures
- Textile-based or paper-based installations

The combination of **low UV emission** and **high CRI** ensures **color accuracy** while safely illuminating artworks over the long

4. Recommended Installation Guidelines

To optimize safety and ensure the longevity of artwork, the following installation guidelines are recommended:

Parameter	Recommendation
Mounting Distance	≥ 1.0 meter from artwork
Lighting Angle	Use indirect, 30°–60° angled lighting
UV Protection	Optional: Install UV-filter glass over artwork for additional protection

These measures help minimize direct UV exposure and reduce the thermal load on the artwork.

5. Conclusion

The [redacted] have been evaluated based on spectrum performance and photobiological safety. With their low UV emission, high CRI, and classification as Exempt Group under IEC 62471, they are deemed safe for use in various applications.:

Safe and suitable for use in art galleries, museums, and similar environments.

The product poses no UV hazard, ensuring safe lighting for artwork preservation.