

SKU	Description	Specification					Tested Data, same as IES Files		
		CCT	CRI	Wattage (W)	Efficacy (lm/w)	Output (lm)	Wattage (W)	Efficacy (lm/w)	Output (lm)
65/1750	WLC05/10/9S3/3S/WH-PHO	3000K	90	10	85	850	10.14	83.04	842.00
		4000K	90	10	95	950	9.57	94.78	907.00
		5000K	90	10	90	900	9.97	84.65	844.00
65/1751	WLC05/10/9S3/3S/BK-PHO	3000K	90	10	85	850	10.14	83.04	842.00
		4000K	90	10	95	950	9.57	94.78	907.00
		5000K	90	10	90	900	9.97	84.65	844.00
65/1752	WLC05/10/9S3/3S/DB-PHO	3000K	90	10	85	850	10.14	83.04	842.00
		4000K	90	10	95	950	9.57	94.78	907.00
		5000K	90	10	90	900	9.97	84.65	844.00
65/1753	WLC05/10/9S3/4S/WH-PHO	3000K	90	10	85	850	10.06	101.09	1017.00
		4000K	90	10	95	950	9.64	113.90	1098.00
		5000K	90	10	90	900	10.02	102.79	1030.00
65/1754	WLC05/10/9S3/4S/BK-PHO	3000K	90	10	85	850	10.06	101.09	1017.00
		4000K	90	10	95	950	9.64	113.90	1098.00
		5000K	90	10	90	900	10.02	102.79	1030.00
65/1755	WLC05/10/9S3/4S/DB-PHO	3000K	90	10	85	850	10.06	101.09	1017.00
		4000K	90	10	95	950	9.64	113.90	1098.00
		5000K	90	10	90	900	10.02	102.79	1030.00
65/1756	WLC05/20/9S3/6S/WH-PHO	3000K	90	10	85	850	18.96	104.32	1978.00
		4000K	90	10	95	950	17.99	117.57	2115.00
		5000K	90	10	90	900	18.76	108.05	2027.00
65/1757	WLC05/20/9S3/6S/BK-PHO	3000K	90	10	85	850	18.96	104.32	1978.00
		4000K	90	10	95	950	17.99	117.57	2115.00
		5000K	90	10	90	900	18.76	108.05	2027.00
65/1758	WLC05/20/9S3/6S/DB-PHO	3000K	90	10	85	850	18.96	104.32	1978.00
		4000K	90	10	95	950	17.99	117.57	2115.00
		5000K	90	10	90	900	18.76	108.05	2027.00
65/1759	WLC05/10/9S3/3D/WH-PHO	3000K	90	10	85	850	9.54	94.76	904.00
		4000K	90	10	95	950	9.30	102.90	957.00
		5000K	90	10	90	900	9.62	98.86	951.00
65/1760	WLC05/10/9S3/3D/BK-PHO	3000K	90	10	85	850	9.54	94.76	904.00
		4000K	90	10	95	950	9.30	102.90	957.00
		5000K	90	10	90	900	9.62	98.86	951.00
65/1761	WLC05/10/9S3/3D/DB-PHO	3000K	90	10	85	850	9.54	94.76	904.00
		4000K	90	10	95	950	9.30	102.90	957.00
		5000K	90	10	90	900	9.62	98.86	951.00
65/1762	WLC05/20/9S3/4D/WH-PHO	3000K	90	20	85	1700	18.87	99.95	1886.00
		4000K	90	20	95	1900	17.92	112.56	2017.00
		5000K	90	20	90	1800	18.67	101.34	1892.00
65/1763	WLC05/20/9S3/4D/BK-PHO	3000K	90	20	85	1700	18.87	99.95	1886.00
		4000K	90	20	95	1900	17.92	112.56	2017.00
		5000K	90	20	90	1800	18.67	101.34	1892.00
65/1764	WLC05/20/9S3/4D/DB-PHO	3000K	90	20	85	1700	18.87	99.95	1886.00
		4000K	90	20	95	1900	17.92	112.56	2017.00
		5000K	90	20	90	1800	18.67	101.34	1892.00
65/1765	WLC05/36/9S3/6D/WH-PHO	3000K	90	36	95	3420	35.28	103.17	3640.00
		4000K	90	36	105	3780	33.43	115.47	3860.00
		5000K	90	36	100	3600	34.57	106.31	3675.00
65/1766	WLC05/36/9S3/6D/BK-PHO	3000K	90	36	95	3420	35.28	103.17	3640.00
		4000K	90	36	105	3780	33.43	115.47	3860.00
		5000K	90	36	100	3600	34.57	106.31	3675.00
65/1767	WLC05/36/9S3/6D/DB-PHO	3000K	90	36	95	3420	35.28	103.17	3640.00
		4000K	90	36	105	3780	33.43	115.47	3860.00
		5000K	90	36	100	3600	34.57	106.31	3675.00