

NEW PRODUCT INFORMATION

Satco LED T8 lamps

Direct replacement for linear fluorescent T8 lamps in existing fixtures with instant or rapid start ballasts. No rewiring required*

Features

- Over 40% energy savings vs standard 4' T8 systems
- All glass tube - eliminating the possibility of yellowing
- Direct replacement solution allows the fixture to maintain the Original UL and CSA Compliance
- Long life- 50,000 hours
- Instant on to full brightness / no flicker
- DLC listed
- 5 year warranty



LED fluorescent replacement lamps

Item Number	Lamp Description	W	CRI	Base Type	Bm	CCT	Lm	M.O.L. (Inches)	Life/Hrs.	UPC
S9234	14T8/LED/48-830/DR	14	82	Med Bi-Pin	230°	3000K	1800	48	50K	045923092343
S9235	14T8/LED/48-835/DR	14	82	Med Bi-Pin	230°	3500K	1800	48	50K	045923092350
S9236	14T8/LED/48-840/DR	14	82	Med Bi-Pin	230°	4000K	1800	48	50K	045923092367
S9237	14T8/LED/48-850/DR	14	82	Med Bi-Pin	230°	5000K	1800	48	50K	045923092374

* May not be compatible with all rapid start ballasts. Contact Satco (800-437-2826) for an approved list.

Pack: Master 10

System Performance

Spec	Item Number	CCT	Nominal Length	Rated Wattage	Rated Lumens	Bare Lamp Wattage			System Watts			Initial Lumens		
						Low Ballast Factor (0.78)	Normal Ballast Factor (0.88)	High Ballast Factor (1.18)	Low Ballast Factor (0.78)	Normal Ballast Factor (0.88)	High Ballast Factor (1.18)	Low Ballast Factor (0.78)	Normal Ballast Factor (0.88)	High Ballast Factor (1.18)
Ballast compatible, 14W, 1800lm	S9234	3000K	4'	14	1800	12.4	14.0	18.8	14.8	17.0	22.4	1500	1710	2170
	S9235	3500K	4'	14	1800	12.4	14.0	18.8	14.8	17.0	22.4	1520	1750	2220
	S9236	4000K	4'	14	1800	12.4	14.0	18.8	14.8	17.0	22.4	1560	1800	2280
	S9237	5000K	4'	14	1800	12.4	14.0	18.8	14.8	17.0	22.4	1590	1840	2320

