

PRODUCT INFORMATION

Omni-directional LED 120-277V A19 lamps


Applications

- Indoor residential and commercial lighting
- Down lighting
- Display lighting
- Accent lighting

Features

- Direct replacement for 60 Watt incandescent lamps, uses only 8.5 Watts
- Direct replacement for 13 Watt screw-in CFL
- Innovative design—smooth heat sink design to resemble traditional incandescent lamp
- 2700K, 3000K, 4000K and 5000K options
- Damp location
- Approved for enclosed fixtures
- 3 year warranty

Non-dimmable



Beam Angle: 220°

Omni-Directional LED A19 Lamps-120-277V



Item Number	Lamp Description	Watt	Volt	CRI	CCT	Lumen	Beam	M.O.L. (Inches)	Life/Hrs.	UPC
S8914*	8.5A19/LED/27K /120-277V	8.5	120-277V	80	2700K	800	220°	4 5/16	25K	045923089145
S8915*	8.5A19/LED/30K /120-277V	8.5	120-277V	80	3000K	800	220°	4 5/16	25K	045923089152
S8916*	8.5A19/LED/40K /120-277V	8.5	120-277V	80	4000K	800	220°	4 5/16	25K	045923089169
S8920*	8.5A19/LED/50K /120-277V	8.5	120-277V	80	5000K	800	220°	4 5/16	25K	045923089206

* ENERGY STAR pending - Aug. '17

Pack: Master 24 / Inner 6/1