

PRODUCT INFORMATION

Satco 6" U-bend LED T8 lamps

Direct replacements for U-bend T8 fluorescent lamps in existing fixtures with instant or rapid start ballasts.

No rewiring required**

Features

- Over 40% energy savings vs. standard T8 systems
- All glass tube
- Direct replacement solution allows the fixture to maintain the Original UL and CSA Compliance
- Long life—50,000 hours
- NSF certified
- c-UL-us listed
- Damp location
- 5 Year warranty



LED T8 6" U-Bend Replacement Lamps



Item Number	Lamp Description	W	CRI	Base Type	Bm	CCT	Lm	M.O.L. (Inches)	Life/Hrs.	UPC	Pack
S9994	11.5T8U6/LED/22.5-830/DR	11.5	82	Med Bi-Pin	230°	3000K	1700	22 ½	50K	045923099946	12
S9995	11.5T8U6/LED/22.5-835/DR	11.5	82	Med Bi-Pin	230°	3500K	1700	22 ½	50K	045923099953	12
S9996	11.5T8U6/LED/22.5-840/DR	11.5	82	Med Bi-Pin	230°	4000K	1800	22 ½	50K	045923099960	12
S9997	11.5T8U6/LED/22.5-850/DR	11.5	82	Med Bi-Pin	230°	5000K	1800	22 ½	50K	045923099977	12

** May not be compatible with all ballasts. Visit www.satco.com for an approved list.

System Performance

						Bare Lamp Wattage			System Watts			Initial Lumens		
Spec	Item Number	CCT	Nominal Length	Rated Wattage	Rated Lumens	Low Ballast Factor (0.78)	Normal Ballast Factor (0.88)	High Ballast Factor (1.18)	Low Ballast Factor (0.78)	Normal Ballast Factor (0.88)	High Ballast Factor (1.18)	Low Ballast Factor (0.78)	Normal Ballast Factor (0.88)	High Ballast Factor (1.18)
Ballast compatible, 11.5W, 1700lm 1800lm,	S9994	3000K	22.5'	11.5	1700	10	11.5	15.4	12.5	13.9	24.1	1510	1680	2180
	S9995	3500K	22.5'	11.5	1700	10	11.5	15.4	12.5	13.9	24.1	1570	1750	2270
	S9996	4000K	22.5'	11.5	1800	10	11.5	15.4	12.5	13.9	24.1	1620	1800	2330
	S9997	5000K	22.5'	11.5	1800	10	11.5	15.4	12.5	13.9	24.1	1620	1800	2330