# **SATCO NUVO**





**CCT SELECTABLE** 

90 CRI

**DIMMABLE** 

**WET LOCATION** 

**50,000 HOURS** 

**5 YEAR WARRANTY** 

SUGGESTED APPLICATIONS Indoor Residential, Multi-Family Living Spaces, Bathrooms, Kitchens and Basements



# LED SLIM FIT DOWNLIGHT WITH REMOTE DRIVER SMOOTH BAFFLE

CCT SELECATBLE - 4" AND 6" ROUND AND SQUARE



The Slim Fit Downlight from SATCO|NUVO delivers an efficient LED solution with its sleek, low-profile design and smooth baffle for uniform light distribution and minimal glare. Offering a range of five color temperatures from 2700K to 5000K, you can customize your lighting environment to your preference. The downlight comes with a remote driver for easy installation and boasts IC and wet ratings for versatile use and safety. Ideal for various indoor settings in homes or multi-family residences, this downlight provides superior light quality with a high CRI of 90. Available in both 4" and 6" sizes, in round or square trims, these dimmable downlights provide a flexible lighting solution to suit your downlighting needs.













## **GENERAL SPECIFICATIONS**

Input Voltage, Frequency: 120V, 60Hz

Dimmable: Down to 10%

**CRI:** 90

**CCT:** 2700K/3000K/3500K/4000K/5000K

Functional Life: 50,000 Hours

**Location Rating:** Wet

Ambient Operating Temperature:  $-20^{\circ}\text{C}$  ( $-4^{\circ}\text{F}$ ) to  $+40^{\circ}\text{C}$  ( $+104^{\circ}\text{F}$ )

**Suitable for Bathroom Applications:** Yes

IC Rated: Yes

Construction: Aluminum Lens Material: Polystyrene

Finish: White Warranty: 5 Year





1.44





## **ITEM SPECIFICATIONS / ORDER INFO**

Item	UPC	Size	Wattage	Replacement Wattage	Lumens	Efficacy	Beam Angle	Case Qty
S11870	045923118708	4" Round	12W	60W	850lm	Up to 71 LPW	112°	12
S11871	045923118715	4" Square	12W	60W	750lm	Up to 63 LPW	110°	12
S11872	045923118722	6" Round	15W	75W	1100lm	Up to 73 LPW	112°	12
S11873	045923118739	6" Square	15W	75W	1000lm	Up to 67 LPW	110°	12

#### **DIMENSIONS**

item	(A/B) Diameter/Length	(C) Height	Weight (Lbs)
S11870	5.06"	1.25"	.92
S11871	5.06"	1.29"	.92
S11872	7.15"	1.25"	.92
S11873	7.17"	1.29"	.92

## **ENERGY SAVINGS** Based on 12 hours/day and \$0.11/kWh

LED Wattage	Incandescent Replacement Wattage	Life (Years)	Yearly Savings
12W	60W	45.7	1.45
15W	75W	45.7	1.81

#### **OPTIONAL ACCESSORIES (SOLD SEPARATELY)**

Item	UPC	Description
80-985	045923809859	6 Foot Remote Driver Extension Cable
80-946	045923809460	4" Round Goof Ring
80-943	045923809439	4" Round Rough-In Mounting Plate with Bars
80-947	045923809477	6" Round Goof Ring
80-944	045923809446	6'' Round Rough-In Mounting Plate with Bars



3 62



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must



6" Goof Ring (80-947)



Remote Driver

Mounting Plate with Bars (80-943, 80-944)

accept any interference received, including interference that may cause undesired operation. Fixture may not be compatible with all dimmers.

4 27"