



**FIELD SELECTABLE
(CCT AND WATTAGE)**

90 CRI

**STEPPED BAFFLE FOR
REDUCED GLARE**

OFFERED IN 4" & 5/6" SIZES

ROUND & SQUARE TRIM OPTIONS

E26 ADAPTER INCLUDED


**4" ROUND MODELS HAVE
ROTATING AND COLLAPSING
TABS FOR SECURE
INSTALLATION AND
EASY REMOVAL**

SUGGESTED APPLICATIONS:

Offices, Retail, Hotels,
Residential, Utility Rooms

LED RETROFIT DOWNLIGHT

FIELD SELECTABLE | STEPPED BAFFLE



SATCO|NUVO's LED Field Selectable Retrofit Downlights are the effortless solution for upgrading recessed lighting in your space. With two on-unit switches, the adjustment of both the input wattage and color temperature is a breeze and allows for the perfect task driven customization of your lighting needs. Offered in 4" and 5/6" models, in round and square trims, the stepped baffle reduces glare and adds dimension to the space. With a traditional look, these downlights will provide beautiful lighting in any environment.



GENERAL SPECIFICATIONS

Input Voltage, Frequency: 120V, 60Hz

Power Factor: 0.9

CCT: 2700K/3000K/3500K/4000K/5000K

Dimmable: Phase-Cut Dimmable Down to 10%

CRI: 90

Beam Angle: 90°

Functional Life: 50,000 Hours

Location Rating: Wet

IC Rated: No

AT Rated: No

Ambient Operating Temperature:

-20°C (-4°F) to +40°C (+104°F)

Finish: White

Lens: Polycarbonate

Lens Finish: Frost

Base: E26 Adapter Included

ITEM SPECIFICATIONS / ORDER INFO



Item	Size	Shape	Lumens @ 3500K	Wattage	Max. Incandescent Replacement Wattage	Efficacy	Input Current	Construction	Case QTY
S18800	4"	Round	500/600/700	5W/6W/7.5W	60W	Up to 100 LPW	0.04/0.05/0.06A	Steel	16
S18802*	4"	Square	500/600/700	5.5W/6.5W/8W	60W	Up to 92 LPW	0.05/0.05/0.07A	Aluminum	16
S18801	5/6"	Round	750/1050/1300	7W/10W/13W	100W	Up to 107 LPW	0.06/0.08/0.11A	Steel	8
S18803*	5/6"	Square	750/1050/1300	7.5W/10.5W/14.5W	100W	Up to 100 LPW	0.06/0.09/0.12A	Aluminum	8

OPTIONAL ACCESSORIES (SOLD SEPARATELY)

Item	Description	Image
80-980	4" Can for New Construction	
80-981	4" Can for Remodel	
80-982	5" Can for New Construction	
80-983	5" Can for Remodel	
S8999	GU24 Adapter	
S9000	GU10 Adapter	
80-2676	Pressure Brackets for RT5 RT6	





This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Fixture may not be compatible with all dimmers.

Replacement wattage shown depends on application and fixture.
Specifications are subject to change without prior notice.

DIMENSIONS/WEIGHTS

Item	Diameter or Width (A)	Height (B)	Weight
S18800	5.31"	2.90"	0.47 Lbs.
S18802	5.31"	3.13"	0.59 Lbs.

4" MODELS







This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Fixture may not be compatible with all dimmers.

Replacement wattage shown depends on application and fixture. Specifications are subject to change without prior notice.

DIMENSIONS/WEIGHTS

Item	Diameter or Width (A)	Height (B)	Weight
S18801	7.40"	3.27"	0.76 Lbs.
S18803	7.13"	3.37"	0.81 Lbs.

5/6" MODELS




This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Fixture may not be compatible with all dimmers.

Replacement wattage shown depends on application and fixture.
Specifications are subject to change without prior notice.

PHOTOMETRICS


SATCO Item: S18800

Description: 7.5LED/RDL/4/WS/5CCT/RD
 Default PowerQuick Setting: 5.9 W
 Default ColorQuick Setting: 2700K
 629 LM, 5.9 W, 107 LPW
 Beam Angle: 96°
 Field Angle: 142°
 Spacing Criteria (0°-180°): 1.16
 Spacing Criteria (90°-270°): 1.19




SATCO Item: S18801

Description: 13LED/RDL/5-6/WS/5CCT/RD
 Default PowerQuick Setting: 10.1 W
 Default ColorQuick Setting: 2700K
 1083 LM, 10.1 W, 107 LPW
 Beam Angle: 97°
 Field Angle: 149°
 Spacing Criteria (0°-180°): 1.22
 Spacing Criteria (90°-270°): 1.20




SATCO Item: S18802

Description: 8LED/RDL/4/WS/5CCT/SQ
 Default PowerQuick Setting: 6.7 W
 Default ColorQuick Setting: 2700K
 706 LM, 6.7 W, 105 LPW
 Beam Angle: 95°
 Field Angle: 150°
 Spacing Criteria (0°-180°): 1.18
 Spacing Criteria (90°-270°): 1.15



SATCO Item: S18803

Description: 14.5LED/RDL/5-6/WS/5CCT/SQ
 Default PowerQuick Setting: 11.1 W
 Default ColorQuick Setting: 2700K
 1183 LM, 11.1 W, 107 LPW
 Beam Angle: 96°
 Field Angle: 152°
 Spacing Criteria (0°-180°): 1.17
 Spacing Criteria (90°-270°): 1.16



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Fixture may not be compatible with all dimmers.

Replacement wattage shown depends on application and fixture.
 Specifications are subject to change without prior notice.