



**FIELD SELECTABLE
(CCT AND WATTAGE)**

**DEEP STEPPED BAFFLE FOR
REDUCED GLARE**

**OFFERED IN 4" & 5/8" SIZES
BOTH ROUND AND SQUARE**

E26 ADAPTER INCLUDED

WET LOCATION RATED


**OPTIONAL COLOR TRIMS SOLD
SEPARATELY**

SUGGESTED APPLICATIONS

Residential, Offices, Retail
Multifamily, Hospitality

LED RETROFIT DOWNLIGHTS

DEEP STEPPED BAFFLE | FIELD SELECTABLE



SATCO|NUVO's LED Field Selectable Deep Baffle Retrofit Downlights are designed with the look of sophistication in mind. The deep stepped baffle crafted on these downlights drastically reduces glare and with a high CRI rating of 90, users can enjoy enhanced brightness, reduced energy consumption and beautiful color renderings in their space. Effortlessly change between three wattage and five color temperature options quickly, with just a flick of the on-unit switches. Change the look of a room easily and cost effectively with our add-on decorative trim accessories. This simple snap-on accessory will not only enhance your décor, but it will allow the fixture to meet Non-Conductive "Dead-Front" code requirements opening code enforced installations. With their timeless aesthetics and exceptional customization capabilities, these downlights promise to deliver stunning illumination in any environment.



GENERAL SPECIFICATIONS

Input Voltage: 120V

Frequency: 60Hz

CCT Selectable: 2700K/3000K/3500K/4000K/5000K

CRI: 90

Dimming: Phase-Cut dimmable down to 10%

THD: <25%

Functional Life: 50,000 Hours

Base: E26 Adapter included

Location Rating: Wet

Ambient Operating Temperature: -20°C (-4°F) to +40°C (+104°F)

Enclosed Fixture Rating: Yes

Suitable for bathroom applications: Yes

Finish: White

Housing: Aluminum

Lens: Polycarbonate







ITEM SPECIFICATIONS / ORDER INFO

Item	Size	Shape	Lumens	Wattage	Replacement Wattage	Power Factor	Input Current	Beam Angle	Efficacy
S11882	4"	Round	600/750/900	5.8W/7W/9.5W	60W	0.94	0.05/0.06/0.08A	75°	Up to 107 LPW
S11883	5/6"	Round	800/1000/1200	8W/10.5W/13.5W	100W	0.96	0.07/0.09/0.12A	75°	Up to 100 LPW
S11884	4"	Square	600/750/900	5.8W/7W/9.5W	60W	0.94	0.05/0.06/0.08A	90°	Up to 107 LPW
S11885	5/6"	Square	800/1000/1200	8W/10.5W/13.5W	100W	0.96	0.07/0.09/0.12A	80°	Up to 100 LPW

DIMENSIONS/WEIGHTS

Item	Length (A)	Diameter or Width (B)	Height (C)	Weight
S11882	-	5.12"	3.25"	0.39 Lbs.
S11883	-	7.20"	4.31"	0.56 Lbs.
S11884	5.31"	5.31"	3.07"	0.51 Lbs.
S11885	7.13"	7.13"	4.21"	0.80 Lbs.



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Fixture may not be compatible with all dimmers.

Replacement wattage shown depends on application and fixture.
Specifications are subject to change without prior notice.


OPTIONAL ACCESSORIES (SOLD SEPARATELY)

Non-Conductive Trim Accessories (When applied to fixture, meets non-conductive code requirements)				
Item	Description	For Use With		
80-974	Deep Baffle 4" Round Trim - Black	S11882		
80-975	Deep Baffle 4" Round Trim - Bronze	S11882		
80-976	Deep Baffle 4" Round Trim - Brushed Nickel	S11882		
80-977	Deep Baffle 5/6" Round Trim - Black	S11883		
80-978	Deep Baffle 5/6" Round Trim - Bronze	S11883		
80-979	Deep Baffle 5/6" Round Trim - Brushed Nickel	S11883		
80-990	Deep Baffle 4" Square Trim - Black	S11884		
80-991	Deep Baffle 4" Square Trim - Bronze	S11884		
80-992	Deep Baffle 4" Square Trim - Brushed Nickel	S11884		
80-993	Deep Baffle 5/6" Square Trim - Black	S11885		
80-994	Deep Baffle 5/6" Square Trim - Bronze	S11885		
80-995	Deep Baffle 5/6" Square Trim - Brushed Nickel	S11885		
Recessed Cans				
Item	Description	For Use With		
80-980	4" ICAT Can for New Construction	S11882, S11884		
80-981	4" ICAT Can for Remodel	S11882, S11884		
80-982	5" ICAT Can for New Construction	S11883, S11885		
80-983	5" ICAT Can for Remodel	S11883, S11885		
Mounting Accessories				
Item	Description	For Use With		
80-2676	Pressure Brackets for 5/6" Downlight Retrofits	S11883, S11885		
S9000	GU10 Adaptor	S11882, S11883, S11884, S11885		

PHOTOMETRICS


SATCO Item: S11882

Description: 9.5WLED/DLR/4/WS/5CCT/RD/DB
 Default PowerQuick Setting: 7.0 W
 Default ColorQuick Setting: 2700K
 740 LM, 7.0 W, 106 LPW
 Beam Angle: 79°
 Field Angle: 126°
 Spacing Criteria (0°-180°): 1.09
 Spacing Criteria (90°-270°): 1.11




SATCO Item: S11883

Description: 13.5WLED/DLR/5-6/WS/5CCT/RD/DB
 Default PowerQuick Setting: 10.5 W
 Default ColorQuick Setting: 2700K
 1012 LM, 10.5 W, 97 LPW
 Beam Angle: 78°
 Field Angle: 123°
 Spacing Criteria (0°-180°): 1.13
 Spacing Criteria (90°-270°): 1.13



SATCO Item: S11884

Description: 9.5WLED/DLR/4/WS/5CCT/SQ/DB
 Default PowerQuick Setting: 7.0 W
 Default ColorQuick Setting: 2700K
 803 LM, 7.0 W, 115 LPW
 Beam Angle: 92°
 Field Angle: 132°
 Spacing Criteria (0°-180°): 1.18
 Spacing Criteria (90°-270°): 1.20



SATCO Item: S11885

Description: 13.5WLED/DLR/5-6/WS/5CCT/SQ/DB
 Default PowerQuick Setting: 10.5 W
 Default ColorQuick Setting: 2700K
 1008 LM, 10.5 W, 96 LPW
 Beam Angle: 80°
 Field Angle: 123°
 Spacing Criteria (0°-180°): 1.12
 Spacing Criteria (90°-270°): 1.12

