



LED | A-SHAPE LAMPS



SATCO® is your single source solution for all of your lighting needs. From emerging LED technologies to decorative fixtures and lighting components, we carry products for nearly every industry and application to our customers. Independent and privately owned for 60 years, SATCO continues to grow because of our traditional values: trust, quality, loyalty and hard work. Agile in practice, unwavering in customer focus...

...we deliver on product, promise & partnership.

60 YEARS IN BUSINESS
100% INDEPENDENT PRIVATELY OWNED
15,000 + PRODUCTS
2 MILLION SQ. FT OF INVENTORY
6 WAREHOUSE LOCATIONS

Table of Contents

A15 40W Replacement	3
A19 40W Replacement	4 - 5
A19 60W Replacement	6 - 9
A19 75W Replacement	10 - 11
A19 100W Replacement	12 - 13
A19 Wattage & CCT Selectable A19 Color Filament	14 - 15
A19, A21, & PS25 3-Way	16 - 17
A19 Specialty Lamps	18 - 19
A21, A25, & PS30 Specialty Lamps	20 - 21
Notes	22 - 23



A15 40W REPLACEMENT

Features:

- Ideal for general purpose, ceiling fans, and appliances
- Create ambiance with smooth dimming
- Excellent color rendering
- Frosted polycarbonate lens



E12 CANDELABRA BASE



E17 INTERMEDIATE BASE



E26 MEDIUM BASE



ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	TITLE 20	PACK SIZE	MOL/ MOD
E12 Candelabra Base Dimmable 120V								
S15200	5.5A15L/827/E12/P/D/1PK	5.5W	450	2700K	80+	No	24/6	A
S15201	5.5A15L/830/E12/P/D/1PK	5.5W	450	3000K	80+	No	24/6	A
S15202	5.5A15L/840/E12/P/D/1PK	5.5W	450	4000K	80+	No	24/6	A
S15203	5.5A15L/850/E12/P/D/1PK	5.5W	450	5000K	80+	No	24/6	A
E17 Intermediate Base Dimmable 120V								
S15204	5.5A15L/827/E17/P/D/1PK	5.5W	450	2700K	80+	No	24/6	A
S15205	5.5A15L/830/E17/P/D/1PK	5.5W	450	3000K	80+	No	24/6	A
S15206	5.5A15L/840/E17/P/D/1PK	5.5W	450	4000K	80+	No	24/6	A
S15207	5.5A15L/850/E17/P/D/1PK	5.5W	450	5000K	80+	No	24/6	A
E26 Medium Base Dimmable 120V								
S15208	5.5A15L/827/E26/P/D/1PK	5.5W	450	2700K	80+	No	24/6	B
S15212	5.5A15L/927/E26/P/D/1PK	5.5W	450	2700K	90+	Yes	24/6	B
S15209	5.5A15L/830/E26/P/D/1PK	5.5W	450	3000K	80+	No	24/6	B
S15213	5.5A15L/930/E26/P/D/1PK	5.5W	450	3000K	90+	Yes	24/6	B
S15210	5.5A15L/840/E26/P/D/1PK	5.5W	450	4000K	80+	No	24/6	B
S15211	5.5A15L/850/E26/P/D/1PK	5.5W	450	5000K	80+	No	24/6	B

90+
CRI

DIMMABLE

DAMP
LOCATION

25,000
HOURS

UL
CERTIFIED

TITLE
20

SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	3.07"	1.77"
B	3.15"	1.77"



A19 | 40W REPLACEMENT

Features:

- CCT Selectable models available
- Excellent color rendering
- Frosted polycarbonate lens



**E26 MEDIUM BASE
(STANDARD)**



**E26 MEDIUM BASE
(5 CCT SELECTABLE)**

NON-DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	TITLE 20	PACK SIZE	MOL / MOD
E26 Medium Base Non-Dimmable 120V								
S14300	5A19L/827/E26/P/ND/1PK	5W	450	2700K	80+	No	24/6	A
S14301	5A19L/827/E26/P/ND/4PK	5W	450	2700K	80+	No	12-4pks	A
S14344	6.5A19L/927/E26/P/ND/1PK	6.5W	450	2700K	90+	Yes	24/6	B
S14345	6.5A19L/927/E26/P/ND/4PK	6.5W	450	2700K	90+	Yes	12-4pks	B
S14302	5A19L/830/E26/P/ND/1PK	5W	450	3000K	80+	No	24/6	A
S14303	5A19L/830/E26/P/ND/4PK	5W	450	3000K	80+	No	12-4pks	A
S14346	6.5A19L/930/E26/P/ND/1PK	6.5W	450	3000K	90+	Yes	24/6	B
S14347	6.5A19L/930/E26/P/ND/4PK	6.5W	450	3000K	90+	Yes	12-4pks	B
S14305	5A19L/840/E26/P/ND/4PK	5W	450	4000K	80+	No	12-4pks	A
S14349	6.5A19L/940/E26/P/ND/4PK	6.5W	450	4000K	90+	Yes	12-4pks	B
S14348	6.5A19L/940/E26/P/ND/1PK	6.5W	450	4000K	90+	Yes	24/6	B
S14306	5A19L/850/E26/P/ND/1PK	5W	450	5000K	80+	No	24/6	A
S14307	5A19L/850/E26/P/ND/4PK	5W	450	5000K	80+	No	12-4pks	A
S14351	6.5A19L/950/E26/P/ND/4PK	6.5W	450	5000K	90+	Yes	12-4pks	B
S14350	6.5A19L/950/E26/P/ND/1PK	6.5W	450	5000K	90+	Yes	24/6	B
S11770R1	6A19L/9CCT5/E26/PWHF	6W	470	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	24/6	C
S11774R1	6A19L/9CCT5/E26/PWHF/4PK	6W	470	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	12-4pks	C



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	3.98"	2.28"
B	4.09"	2.36"
C	4.13"	2.36"

DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	TITLE 20	T24/JA8	PACK SIZE	MOL / MOD
E26 Medium Base Dimmable 120V									
S15130	6A19L/827/E26/P/D/1PK	6W	450	2700K	80+	Yes	No	24/6	A
S15135	5.5A19L/927/E26/P/D/1PK	5.5W	450	2700K	90+	Yes	Yes	24/6	B
S15131	6A19L/830/E26/P/D/1PK	6W	450	3000K	80+	Yes	No	24/6	A
S15136	5.5A19L/930/E26/P/D/1PK	5.5W	450	3000K	90+	Yes	Yes	24/6	B
S15132	6A19L/835/E26/P/D/1PK	6W	450	3500K	80+	Yes	No	24/6	A
S15133	6A19L/840/E26/P/D/1PK	6W	450	4000K	80+	Yes	No	24/6	A
S15134	6A19L/850/E26/P/D/1PK	6W	450	5000K	80+	Yes	No	24/6	A
S15188	6A19L/8CCT5/E26/P/D/1PK	6W	450	2700K/3000K/3500K/4000K/5000K	80+	Yes	No	24/6	B
S15192	6A19L/9CCT5/E26/P/D/1PK	6W	450	2700K/3000K/3500K/4000K/5000K	90+	Yes	No	24/6	B
S15196	5.8A19L/9CCT5/E26/P/D/1PK	5.8W	470	2700K/3000K/3500K/4000K/5000K	90+	Yes	Yes	24/6	C



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.13"	2.36"
B	4.17"	2.36"
C	4.41"	2.36"



A19 | 60W REPLACEMENT

Features:

- 120V and 120-277V models available
- CCT Selectable models available
- Excellent color rendering
- Frosted polycarbonate lens



E26 MEDIUM BASE
(STANDARD)



E26 MEDIUM BASE
(5 CCT SELECTABLE)

NON-DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	TITLE 20	PACK SIZE	MOL / MOD
E26 Medium Base Non-Dimmable 120V								
S14308	8.5A19L/827/E26/P/ND/1PK	8.5W	800	2700K	80+	No	24/6	A
S14309	8.5A19L/827/E26/P/ND/4PK	8.5W	800	2700K	80+	No	12-4pks	A
S14310	8.5A19L/827/E26/P/ND/12PK	8.5W	800	2700K	80+	No	4-12pks	A
S14311	8.5A19L/827/E26/P/ND/100PK	8.5W	800	2700K	80+	No	1-100pk	A
S11434	9.8A19L/827/ECO/ND/2PK	9.8W	800	2700K	80+	No	24	E
S14352	9.8A19L/927/E26/P/ND/1PK	9.8W	800	2700K	90+	Yes	24/6	E
S14353	9.8A19L/927/E26/P/ND/4PK	9.8W	800	2700K	90+	Yes	12-4pks	E
S14354	9.8A19L/927/E26/P/ND/12PK	9.8W	800	2700K	90+	Yes	4-12pks	E
S14413	9.8A19L/927/E26/P/ND/100PK	9.8W	800	2700K	90+	Yes	1-100pk	E
S14312	8.5A19L/830/E26/P/ND/1PK	8.5W	800	3000K	80+	No	24/6	A
S14313	8.5A19L/830/E26/P/ND/4PK	8.5W	800	3000K	80+	No	12-4pks	A
S14314	8.5A19L/830/E26/P/ND/12PK	8.5W	800	3000K	80+	No	4-12pks	A
S14411	8.5A19L/830/E26/P/ND/100PK	8.5W	800	3000K	80+	No	1-100pk	A
S14355	9.8A19L/930/E26/P/ND/1PK	9.8W	800	3000K	90+	Yes	24/6	E
S14356	9.8A19L/930/E26/P/ND/4PK	9.8W	800	3000K	90+	Yes	12-4pks	E
S14357	9.8A19L/930/E26/P/ND/12PK	9.8W	800	3000K	90+	Yes	4-12pks	E
S14414	9.8A19L/930/E26/P/ND/100PK	9.8W	800	3000K	90+	Yes	1-100pk	E
S14315	8.5A19L/840/E26/P/ND/1PK	8.5W	800	4000K	80+	No	24/6	A
S14316	8.5A19L/840/E26/P/ND/4PK	8.5W	800	4000K	80+	No	12-4pks	A
S14317	8.5A19L/840/E26/P/ND/12PK	8.5W	800	4000K	80+	No	4-12pks	A
S14318	8.5A19L/840/E26/P/ND/100PK	8.5W	800	4000K	80+	No	1-100pk	A
S14358	9.8A19L/940/E26/P/ND/1PK	9.8W	800	4000K	90+	Yes	24/6	E
S14359	9.8A19L/940/E26/P/ND/4PK	9.8W	800	4000K	90+	Yes	12-4pks	E
S14360	9.8A19L/940/E26/P/ND/12PK	9.8W	800	4000K	90+	Yes	4-12pks	E
S14415	9.8A19L/940/E26/P/ND/100PK	9.8W	800	4000K	90+	Yes	1-100pk	E
S14319	8.5A19L/850/E26/P/ND/1PK	8.5W	800	5000K	80+	No	24/6	A
S14320	8.5A19L/850/E26/P/ND/4PK	8.5W	800	5000K	80+	No	12-4pks	A
S14321	8.5A19L/850/E26/P/ND/12PK	8.5W	800	5000K	80+	No	4-12pks	B
S14412	8.5A19L/850/E26/P/ND/100PK	8.5W	800	5000K	80+	No	1-100pk	B
S14361	9.8A19L/950/E26/P/ND/1PK	9.8W	800	5000K	90+	Yes	24/6	E
S14362	9.8A19L/950/E26/P/ND/4PK	9.8W	800	5000K	90+	Yes	12-4pks	E
S14363	9.8A19L/950/E26/P/ND/12PK	9.8W	800	5000K	90+	Yes	4-12pks	E
S14416	9.8A19L/950/E26/P/ND/100PK	9.8W	800	5000K	90+	Yes	1-100pk	E
S11771R1	9A19L/9CCT5/E26/PWHF	9W	800	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	24/6	F
S11775R1	9A19L/9CCT5/E26/PWHF/4PK	9W	800	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	12-4pks	E
E26 Medium Base Non-Dimmable 120-277V								
S14364	9.8A19L/927/E26/P/NDU/1PK	9.8W	800	2700K	90+	Yes	24/6	E
S14365	9.8A19L/930/E26/P/NDU/1PK	9.8W	800	3000K	90+	Yes	24/6	E
S14366	9.8A19L/940/E26/P/NDU/1PK	9.8W	800	4000K	90+	Yes	24/6	D
S14367	9.8A19L/950/E26/P/NDU/1PK	9.8W	800	5000K	90+	Yes	24/6	C



Intertek

SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	3.98"	2.28"
B	4.13"	2.36"
C	4.16"	2.32"
D	4.16"	2.33"
E	4.17"	2.32"
F	4.33"	2.36"



A19 | 60W REPLACEMENT

Features:

- E12, E26, and GU24 bases available
- CCT Selectable models available
- Excellent color rendering
- Frosted polycarbonate lens



E12 CANDELABRA BASE
(STANDARD)



E26 MEDIUM BASE
(5 CCT SELECTABLE)



GU24 BASE
(STANDARD)

DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	T24/ JA8	PACK SIZE	MOL / MOD
E12 Candelabra Base Dimmable 120V								
S15146	9.5A19L/827/E12/P/D/1PK	9.5W	800	2700K	80+	No	24/6	A
S15147	9.5A19L/830/E12/P/D/1PK	9.5W	800	3000K	80+	No	24/6	A
S15148	9.5A19L/840/E12/P/D/1PK	9.5W	800	4000K	80+	No	24/6	A
S15149	9.5A19L/850/E12/P/D/1PK	9.5W	800	5000K	80+	No	24/6	A
E26 Medium Base Dimmable 120V								
S15137	9.5A19L/827/E26/P/D/1PK	9.5W	800	2700K	80+	No	24/6	D
S15138	9.5A19L/827/E26/P/D/4PK	9.5W	800	2700K	80+	No	12-4pks	D
S15155	9.4A19L/927/E26/P/D/1PK	9.4W	800	2700K	90+	Yes	24/6	D
S15150	9.5A19L/927/E26/P/D/1PK	9.5W	800	2700K	90+	No	24/6	D
S15139	9.5A19L/830/E26/P/D/1PK	9.5W	800	3000K	80+	No	24/6	D
S15140	9.5A19L/830/E26/P/D/4PK	9.5W	800	3000K	80+	No	12-4pks	D
S15156	9.4A19L/930/E26/P/D/1PK	9.4W	800	3000K	90+	Yes	24/6	D
S15151	9.5A19L/930/E26/P/D/1PK	9.5W	800	3000K	90+	No	24/6	D
S15141	9.5A19L/835/E26/P/D/1PK	9.5W	800	3500K	80+	No	24/6	D
S15152	9.5A19L/935/E26/P/D/1PK	9.5W	800	3500K	90+	No	24/6	D
S15142	9.5A19L/840/E26/P/D/1PK	9.5W	800	4000K	80+	No	24/6	D
S15143	9.5A19L/840/E26/P/D/4PK	9.5W	800	4000K	80+	No	12/4	D
S15157	9.4A19L/940/E26/P/D/1PK	9.4W	800	4000K	90+	Yes	24/6	D
S15153	9.5A19L/940/E26/P/D/1PK	9.5W	800	4000K	90+	No	24/6	D
S15144	9.5A19L/850/E26/P/D/1PK	9.5W	800	5000K	80+	No	24/6	D
S15145	9.5A19L/850/E26/P/D/4PK	9.5W	800	5000K	80+	No	12-4pks	D
S15154	9.5A19L/950/E26/P/D/1PK	9.5W	800	5000K	90+	No	24/6	D
S15189	9.5A19L/8CCT5/E26/P/D/1PK	9.5W	800	2700K/3000K/3500K/ 4000K/5000K	80+	No	24/6	C
S15197	9.4A19L/9CCT5/E26/P/D/1PK	9.4W	800	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	24/6	C
S15193	9.5A19L/9CCT5/E26/P/D/1PK	9.5W	800	2700K/3000K/3500K/ 4000K/5000K	90+	No	24/6	C
GU24 Base Dimmable 120V								
S15214	9.5A19L/927/GU24/P/D/1PK	9.5W	800	2700K	90+	No	24/6	E
S15215	9.5A19L/930/GU24/P/D/1PK	9.5W	800	3000K	90+	No	24/6	E
S15216	9.5A19L/935/GU24/P/D/1PK	9.5W	800	3500K	90+	No	24/6	E
S15217	9.5A19L/940/GU24/P/D/1PK	9.5W	800	4000K	90+	No	24/6	E
S15218	9.5A19L/950/GU24/P/D/1PK	9.5W	800	5000K	90+	No	24/6	E
S15223	9.5A19L/9CCT5/GU24/P/D/1PK	9.5W	800	2700K/3000K/3500K/ 4000K/5000K	90+	No	24/6	B



Intertek

SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.72"	2.36"
B	4.07"	2.36"
C	4.17"	2.32"
D	4.21"	2.36"
E	4.33"	2.36"



A19 | 75W REPLACEMENT

Features:

- E26 and GU24 bases
- Dimmable and Non-Dimmable models
- Excellent color rendering
- Frosted polycarbonate lens



E26 MEDIUM BASE
(STANDARD)



E26 MEDIUM BASE
(5 CCT SELECTABLE)



GU24 BASE
(STANDARD)

NON-DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	SAFETY LISTING	TITLE 20	PACK SIZE	MOL / MOD
E26 Medium Base Non-Dimmable 120V									
S14322	12A19L/827/E26/P/ND/1PK	12W	1100	2700K	80+	cETLus	No	24/6	A
S14323	12A19L/827/E26/P/ND/4PK	12W	1100	2700K	80+	cETLus	No	12-4pks	A
S14368	13.5A19L/927/E26/P/ND/1PK	13.5W	1100	2700K	90+	cETLus	Yes	24/6	B
S14369	13.5A19L/927/E26/P/ND/4PK	13.5W	1100	2700K	90+	cETLus	Yes	12-4pks	B
S14324	12A19L/830/E26/P/ND/1PK	12W	1100	3000K	80+	cETLus	No	24/6	A
S14325	12A19L/830/E26/P/ND/4PK	12W	1100	3000K	80+	cETLus	No	12-4pks	A
S14326	12A19L/830/E26/P/ND/12PK	12W	1100	3000K	80+	cETLus	No	4-12pks	A
S14370	13.5A19L/930/E26/P/ND/1PK	13.5W	1100	3000K	90+	cETLus	Yes	24/6	B
S14371	13.5A19L/930/E26/P/ND/4PK	13.5W	1100	3000K	90+	cETLus	Yes	12-4pks	B
S14327	12A19L/840/E26/P/ND/1PK	12W	1100	4000K	80+	cETLus	No	24/6	A
S14328	12A19L/840/E26/P/ND/4PK	12W	1100	4000K	80+	cETLus	No	12-4pks	A
S14372	13.5A19L/940/E26/P/ND/1PK	13.5W	1100	4000K	90+	cETLus	Yes	24/6	B
S14373	13.5A19L/940/E26/P/ND/4PK	13.5W	1100	4000K	90+	cETLus	Yes	12-4pks	B
S14329	12A19L/850/E26/P/ND/1PK	12W	1100	5000K	80+	cETLus	No	24/6	A
S14330	12A19L/850/E26/P/ND/4PK	12W	1100	5000K	80+	cETLus	No	12-4pks	A
S14331	12A19L/850/E26/P/ND/12PK	12W	1100	5000K	80+	cETLus	No	4-12pks	A
S14374	13.5A19L/950/E26/P/ND/1PK	13.5W	1100	5000K	90+	cETLus	Yes	24/6	B
S14375	13.5A19L/950/E26/P/ND/4PK	13.5W	1100	5000K	90+	cETLus	Yes	12-4pks	B
S11772R1	12A19L/9CCT5/E26/PWHF	12W	1100	2700K/3000K/3500K/4000K/5000K	90+	cULus	Yes	24/6	C
S11776R1	12A19L/9CCT5/E26/PWHF/4PK	12W	1100	2700K/3000K/3500K/4000K/5000K	90+	cULus	Yes	12-4pks	C



Intertek

SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	3.98"	2.28"
B	4.53"	2.36"
C	4.61"	2.36"

DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	PACK SIZE	MOL / MOD
E26 Medium Base Dimmable 120V							
S15158	12A19L/827/E26/P/D/1PK	12W	1100	2700K	80+	24/6	B
S15159	12A19L/827/E26/P/D/4PK	12W	1100	2700K	80+	12-4pks	B
S15170	11.9A19L/927/E26/P/D/1PK	11.9W	1100	2700K	90+	24/6	D
S15166	12A19L/927/E26/P/D/1PK	12W	1100	2700K	90+	24/6	B
S15160	12A19L/830/E26/P/D/1PK	12W	1100	3000K	80+	24/6	B
S15161	12A19L/830/E26/P/D/4PK	12W	1100	3000K	80+	12-4pks	B
S15171	11.9A19L/930/E26/P/D/1PK	11.9W	1100	3000K	90+	24/6	D
S15167	12A19L/930/E26/P/D/1PK	12W	1100	3000K	90+	24/6	B
S15162	12A19L/840/E26/P/D/1PK	12W	1100	4000K	80+	24/6	B
S15163	12A19L/840/E26/P/D/4PK	12W	1100	4000K	80+	12-4pks	B
S15172	11.9A19L/940/E26/P/D/1PK	11.9W	1100	4000K	90+	24/6	D
S15168	12A19L/940/E26/P/D/1PK	12W	1100	4000K	90+	24/6	B
S15164	12A19L/850/E26/P/D/1PK	12W	1100	5000K	80+	24/6	B
S15165	12A19L/850/E26/P/D/4PK	12W	1100	5000K	80+	12-4pks	B
S15169	12A19L/950/E26/P/D/1PK	12W	1100	5000K	90+	24/6	B
S15190	12A19L/8CCT5/E26/P/D/1PK	12W	1100	2700K/3000K/3500K/4000K/5000K	80+	24/6	E
S15198	11.9A19L/9CCT5/E26/P/D/1PK	11.9W	1100	2700K/3000K/3500K/4000K/5000K	90+	24/6	E
S15194	12A19L/9CCT5/E26/P/D/1PK	12W	1100	2700K/3000K/3500K/4000K/5000K	90+	24/6	E
GU24 Base Dimmable 120V							
S15219	12A19L/927/GU24/P/D/1PK	12W	1100	2700K	90+	24/6	C
S15220	12A19L/940/GU24/P/D/1PK	12W	1100	4000K	90+	24/6	C
S15224	12A19L/9CCT5/GU24/P/D/1PK	12W	1100	2700K/3000K/3500K/4000K/5000K	90+	24/6	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.07"	2.36"
B	4.21"	2.28"
C	4.33"	2.36"
D	4.41"	2.36"
E	4.61"	2.36"



A19 | 100W REPLACEMENT

Features:

- E26 and GU24 bases
- Dimmable and Non-Dimmable models
- CCT Selectable models available
- Excellent color rendering
- Frosted polycarbonate lens



E26 MEDIUM BASE
(STANDARD)



E26 MEDIUM BASE
(5 CCT SELECTABLE)



GU24 BASE
(STANDARD)

NON-DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	SAFETY LISTING	TITLE 20	PACK SIZE	MOL/ MOD
E26 Medium Base Non-Dimmable 120V									
S14332	15A19L/827/E26/P/ND/1PK	15W	1600	2700K	80+	cETLus - Listed	No	24/6	A
S14333	15A19L/827/E26/P/ND/4PK	15W	1600	2700K	80+	cETLus - Listed	No	12-4pks	A
S14334	15A19L/827/E26/P/ND/12PK	15W	1600	2700K	80+	cETLus - Listed	No	4-12pks	A
S14383	16.5A19L/927/E26/P/ND/1PK	16.5W	1500	2700K	90+	cETLus - Listed	Yes	24/6	B
S14376	16.5A19L/927/E26/P/ND/4PK	16.5W	1500	2700K	90+	cETLus - Listed	Yes	12-4pks	B
S14335	15A19L/830/E26/P/ND/1PK	15W	1600	3000K	80+	cETLus - Listed	No	24/6	A
S14336	15A19L/830/E26/P/ND/4PK	15W	1600	3000K	80+	cETLus - Listed	No	12-4pks	A
S14337	15A19L/830/E26/P/ND/12PK	15W	1600	3000K	80+	cETLus - Listed	No	4-12pks	A
S14377	16.5A19L/930/E26/P/ND/1PK	16.5W	1500	3000K	90+	cETLus - Listed	Yes	24/6	B
S14378	16.5A19L/930/E26/P/ND/4PK	16.5W	1500	3000K	90+	cETLus - Listed	Yes	12-4pks	B
S14338	15A19L/840/E26/P/ND/1PK	15W	1600	4000K	80+	cETLus - Listed	No	24/6	A
S14339	15A19L/840/E26/P/ND/4PK	15W	1600	4000K	80+	cETLus - Listed	No	12-4pks	A
S14340	15A19L/840/E26/P/ND/12PK	15W	1600	4000K	80+	cETLus - Listed	No	4-12pks	A
S14379	16.5A19L/940/E26/P/ND/1PK	16.5W	1500	4000K	90+	cETLus - Listed	Yes	24/6	B
S14380	16.5A19L/940/E26/P/ND/4PK	16.5W	1500	4000K	90+	cETLus - Listed	Yes	12-4pks	B
S14341	15A19L/850/E26/P/ND/1PK	15W	1600	5000K	80+	cETLus - Listed	No	24/6	A
S14342	15A19L/850/E26/P/ND/4PK	15W	1600	5000K	80+	cETLus - Listed	No	12-4pks	A
S14343	15A19L/850/E26/P/ND/12PK	15W	1600	5000K	80+	cETLus - Listed	No	4-12pks	A
S14381	16.5A19L/950/E26/P/ND/1PK	16.5W	1500	5000K	90+	cETLus - Listed	Yes	24/6	B
S14382	16.5A19L/950/E26/P/ND/4PK	16.5W	1500	5000K	90+	cETLus - Listed	Yes	12-4pks	B
S11773R1	14A19L/9CCT5/E26/PWHF	14W	1500	2700K/3000K/3500K/ 4000K/5000K	90+	cULus	Yes	24/6	C
S11777R1	14A19L/9CCT5/E26/PWHF/4PK	14W	1500	2700K/3000K/3500K/ 4000K/5000K	90+	cULus	Yes	12-4pks	C



Intertek

SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.45"	2.32"
B	4.53"	2.36"
C	4.61"	2.36"

DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	TITLE 20	T24/JA8	PACK SIZE	MOL/ MOD
E26 Medium Base Dimmable 120V									
S15173	14A19L/827/E26/P/D/1PK	14W	1600	2700K	80+	No	No	24/6	C
S15174	14A19L/827/E26/P/D/4PK	14W	1600	2700K	80+	No	No	12-4pks	C
S15185	13.9A19L/927/E26/P/D/1PK	13.9W	1600	2700K	90+	Yes	Yes	24/6	D
S15181	14A19L/927/E26/P/D/1PK	14W	1600	2700K	90+	Yes	No	24/6	C
S15175	14A19L/830/E26/P/D/1PK	14W	1600	3000K	80+	No	No	24/6	C
S15176	14A19L/830/E26/P/D/4PK	14W	1600	3000K	80+	No	No	12-4pks	C
S15186	13.9A19L/930/E26/P/D/1PK	13.9W	1600	3000K	90+	Yes	Yes	24/6	D
S15182	14A19L/930/E26/P/D/1PK	14W	1600	3000K	90+	Yes	No	24/6	C
S15177	14A19L/840/E26/P/D/1PK	14W	1600	4000K	80+	No	No	24/6	C
S15178	14A19L/840/E26/P/D/4PK	14W	1600	4000K	80+	No	No	12-4pks	C
S15187	13.9A19L/940/E26/P/D/1PK	13.9W	1600	4000K	90+	Yes	Yes	24/6	D
S15183	14A19L/940/E26/P/D/1PK	14W	1600	4000K	90+	Yes	No	24/6	C
S15179	14A19L/850/E26/P/D/1PK	14W	1600	5000K	80+	No	No	24/6	C
S15180	14A19L/850/E26/P/D/4PK	14W	1600	5000K	80+	No	No	12-4pks	C
S15184	14A19L/950/E26/P/D/1PK	14W	1600	5000K	90+	Yes	No	24/6	C
S15191	14A19L/8CCT5/E26/P/D/1PK	14W	1600	2700K/3000K/3500K/ 4000K/5000K	80+	No	No	24/6	D
S15199	13.9A19L/9CCT5/E26/P/D/1PK	13.9W	1500	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	Yes	24/6	D
S15195	14A19L/9CCT5/E26/P/D/1PK	14W	1600	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	No	24/6	D
GU24 Bi-Pin Base Dimmable 120V									
S15221	14A19L/927/GU24/P/D/1PK	14W	1600	2700K	90+	Yes	No	24/6	B
S15222	14A19L/940/GU24/P/D/1PK	14W	1600	4000K	90+	Yes	No	24/6	B
S15225	14A19L/9CCT5/GU24/P/D/1PK	14W	1500	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	No	24/6	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.07"	2.36"
B	4.33"	2.36"
C	4.57"	2.36"
D	4.61"	2.36"



A19 | WATTAGE & CCT SELECTABLE

Features:

- Replaces 100W-40W lamps
- More options in one lamp
- Easy SKU reduction
- Frosted polycarbonate lens



E26 MEDIUM BASE
(4 WATTAGE | 6 CCT SELECTABLE)

SIDE 1
(4 WATTAGE SELECTABLE)



SIDE 2
(6 CCT SELECTABLE)



ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	TITLE 20	PACK SIZE	MOL / MOD
E26 Medium Base Dimmable 120V								
S15226	15SA19L/8CCT6/E26/P/D/1PK	15W/11W/8W/5W	1500/1100/800/450	2700K/3000K/3500K/4000K/5000K/6500K	80+	No	24/6	A
S15227	15SA19L/9CCT6/E26/P/D/1PK	15W/11W/8W/5W	1500/1100/800/450	2700K/3000K/3500K/4000K/5000K/6500K	90+	Yes	24/6	A

90+ CRI

CCT SELECTABLE

DIMMABLE

DAMP LOCATION

25,000 HOURS

CERTIFIED

TITLE 20

SIZE LEGEND

LENGTH (MOL)

DIAMETER (MOD)

A

4.61"

2.38"



A19 | COLOR FILAMENT

Features:

- Clear glass bulb
- Color filament emits color light
- Celebrate your favorite holiday, party, or team



S14384
(RED)



S14385
(ORANGE)



S14386
(YELLOW)



S14387
(GREEN)



S14388
(BLUE)



S14389
(PURPLE)



S14390
(PINK)



S14391
(BLACK)



ITEM	DESCRIPTION	COLOR	WATTS	PACK SIZE	MOL / MOD
E26 Medium Base Non-Dimmable 120V					
S14384	8A19L/E26/GCRS/ND/1PK	Red	8W	24/6	A
S14385	8A19L/E26/GCOS/ND/1PK	Orange	8W	24/6	A
S14386	8A19L/E26/GCYS/ND/1PK	Yellow	8W	24/6	A
S14387	8A19L/E26/GCGNS/ND/1PK	Green	8W	24/6	A
S14388	8A19L/E26/GCBLS/ND/1PK	Blue	8W	24/6	A
S14389	8A19L/E26/GCPUS/ND/1PK	Purple	8W	24/6	A
S14390	8A19L/E26/GCPIS/ND/1PK	Pink	8W	24/6	A
S14391	6A19L/E26/GCBKS/ND/1PK	Black	6W	24/6	A



**15,000
HOURS**



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.29"	2.36"



A19, A21, & PS25 | 3-WAY

Features:

- Classic 3-way function with compatible fixtures
- E26D and E39D bases
- CCT Selectable models available
- Dimmable and Non-Dimmable models available



E26 MEDIUM BASE
(STANDARD)



E26 MEDIUM BASE
(5 CCT SELECTABLE)



E39D BASE
(STANDARD)

NON-DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	TITLE 20	PACK SIZE	MOL / MOD
100/70/30W Replacement A19 E26D Medium Base Non-Dimmable 120V								
S14402	13.5SA19/927/E26D/P/ND/3WY/1PK	13.5W/10W/5W	1100/800/450	2700K	90+	Yes	24/6	B
S14393	13.5SA19/830/E26D/P/ND/3WY/1PK	13.5W/10W/5W	1100/800/450	3000K	80+	No	24/6	A
S14403	13.5SA19/930/E26D/P/ND/3WY/1PK	13.5W/10W/5W	1100/800/450	3000K	90+	Yes	24/6	B
S14394	13.5SA19/840/E26D/P/ND/3WY/1PK	13.5W/10W/5W	1100/800/450	4000K	80+	No	24/6	A
S14395	13.5SA19/850/E26D/P/ND/3WY/1PK	13.5W/10W/5W	1100/800/450	5000K	80+	No	24/6	A
S14396	13.5SA19/8CCT5/E26D/P/ND3WY1PK	13.5W/10W/5W	1100/800/450	2700K/3000K/3500K/ 4000K/5000K	80+	No	24/6	C
S14404	13.5SA19/9CCT5/E26D/P/ND3WY1PK	13.5W/10W/5W	1100/800/450	2700K/3000K/3500K/ 4000K/5000K	90+	Yes	24/6	D



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.45"	2.32"
B	4.53"	2.36"
C	4.61"	2.32"
D	4.65"	2.36"
E	4.69"	2.36"

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	AVERAGE RATED HRS.	TITLE 20	PACK SIZE	MOL / MOD
150/100/50W Replacement A21 E26D Medium Base Non-Dimmable 120V									
S14397	20A21/827/E26D/P/ND/3WAY/1PK	20W/14W/6.5W	2150/1600/625	2700K	80+	15000	No	24/6	B
S14398	20A21/830/E26D/P/ND/3WAY/1PK	20W/14W/6.5W	2150/1600/625	3000K	80+	15000	No	24/6	B
S14399	20A21/840/E26D/P/ND/3WAY/1PK	20W/14W/6.5W	2150/1600/625	4000K	80+	15000	No	24/6	B
S11517	5/14/20A21/3-WAY/LED/940	5W/14W/20W	2150/1600/600	4000K	90+	25000	Exempt	24/6	A
S11518	5/14/20A21/3-WAY/LED/950	5W/14W/20W	2150/1600/600	5000K	90+	25000	Exempt	24/6	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.45"	2.32"
B	4.53"	2.36"
C	4.61"	2.32"

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	PACK SIZE	MOL / MOD
100/200/300W Replacement PS25 E39D Base Non-Dimmable 120V							
S11490R1	10/22/33PS25/3WAY/LED/827/E39D	10W/22W/33W	1300/2900/4000	2700K	80+	12/6	A
S11491R1	10/22/33PS25/3WAY/LED/830/E39D	10W/22W/33W	1300/2900/4000	3000K	80+	12/6	A
S11492R1	10/22/33PS25/3WAY/LED/840/E39D	10W/22W/33W	1300/2900/4000	4000K	80+	12/6	A
S11493R1	10/22/33PS25/3WAY/LED/850/E39D	10W/22W/33W	1300/2900/4000	5000K	80+	12/6	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	6.61"	3.11"



A19 | SPECIALTY LAMPS

Features:

- Wide variety for many applications
- Frosted polycarbonate lens



LOW VOLTAGE
(STANDARD)



LEFT HAND THREADED
(5 CCT SELECTABLE)



MOTION SENSOR LAMP
(STANDARD)



AGRICULTURE LAMP
(STANDARD)

NON-DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	PACK SIZE	MOL / MOD
Low Voltage							
E26 Medium Base Non-Dimmable 12-34V							
S14405	9A19L/827/E26/P/ND12-34V/1PK	9W	800	2700K	80+	24/6	A
S14406	9A19L/840/E26/P/ND12-34V/1PK	9W	800	4000K	80+	24/6	A
S14407	9A19L/8CCT5/E26/P/ND12-34V/1PK	9W	800	2700K/3000K/3500K/ 4000K/5000K	80+	24/6	B
S14408	15A19L/827/E26/P/ND12-34V/1PK	15W	1600	2700K	80+	24/6	C
S14409	15A19L/840/E26/P/ND12-34V/1PK	15W	1600	4000K	80+	24/6	C
S14410	15A19L/8CCT5/E26/P/ND12-34V/1PK	15W	1600	2700K/3000K/3500K/ 4000K/5000K	80+	24/6	D



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	3.98"	2.28"
B	4.45"	2.28"
C	4.45"	2.32"
D	4.61"	2.32"

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	SAFETY LISTING	PACK SIZE	MOL / MOD
Left Hand Threaded								
E26 Medium Base Non-Dimmable 120V								
S11315	10WA19L/8CCT5/E26/P/ND/LHT/1PK	10W	1050	2700K/3000K/3500K/ 4000K/5000K	80+	cETLus	24/6	B



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.56"	2.38"
B	4.61"	2.32"

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	SAFETY LISTING	TITLE 20	PACK SIZE	MOL / MOD
Motion Sensor									
E26 Medium Base Non-Dimmable 120V									
S11445	12A19/PIR/930/120V/ND	12W	1050	3000K	90+	cULus	Yes	24/6	A
S11446	12A19/PIR/950/120V/ND	12W	1050	5000K	90+	cULus	Yes	24/6	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	5.11"	2.36"

DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	SAFETY LISTING	PACK SIZE	MOD / MOL
Agriculture								
E26 Medium Base Dimmable 120V								
S11430	5A19/LED/827/AGRI/120V/D	5W	550	2700K	80+	cULus	48/12	A
S11432	8.5A19/LED/827/AGRI/120V/D	8.5W	1000	2700K	80+	cULus	48/12	A
S11433	8.5A19/LED/850/AGRI/120V/D	8.5W	1000	5000K	80+	cULus	48/12	A
S11458	10.5A19/LED/827/AGRI/120V/D	10.5W	1600	2700K	80+	cULus	48/12	A
S11459	10.5A19/LED/850/AGRI/120V/D	10.5W	1600	5000K	80+	cULus	48/12	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	4.61"	2.36"



A21, A25, & PS30 | SPECIALTY LAMPS

Features:

- Great for a variety of applications
- Frosted polycarbonate lens



A21 60W | E26 MEDIUM BASE
(BATTERY BACKUP)



A21 125W | E26 MEDIUM BASE
(STANDARD)



A25 300W | E26 MEDIUM BASE
(NON-DIMMABLE)



PS30 300W | E26 MEDIUM BASE
(DIMMABLE)

NON-DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	PACK SIZE	MOL / MOD
Battery Backup A21 60W Replacement E26 Base Non-Dimmable 120V							
S11468	8A21/BATTERY BU/LED/830	8W	760	3000K	80+	24/6	A
S11469	8A21/BATTERY BU/LED/850	8W	760	5000K	80+	24/6	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	5.59"	2.60"

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	PACK SIZE	MOL / MOD
A21 125W Replacement E26 Medium Base Non-Dimmable 120-277V							
S11329	20A21/LED/927/120-277V/ND	20W	2000	2700K	90+	24/6	A
S11330	20A21/LED/930/120-277V/ND	20W	2000	3000K	90+	24/6	A
S11331	20A21/LED/940/120-277V/ND	20W	2000	4000K	90+	24/6	A
S11332	20A21/LED/950/120-277V/ND	20W	2000	5000K	90+	24/6	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	5.55"	2.63"

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	PACK SIZE	MOL / MOD
A25 300W Replacement E26 Medium Base Non-Dimmable 120V							
S11465	30A25/LED/830/120V/ND	30W	3750	3000K	80+	24/12	A
S11467	30A25/LED/850/120V/ND	30W	3750	5000K	80+	24/12	A



SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	7.32"	3.75"


DIMMABLE

ITEM	DESCRIPTION	WATTS	LUMENS	CCT	CRI	PACK SIZE	MOL / MOD
PS30 300W Replacement E26 Medium Base Dimmable 120V							
S11480	36PS30/LED/827/120V/DIM/E26	36W	4500	2700K	80+	24/12	A
S11481	36PS30/LED/840/120V/DIM/E26	36W	4500	4000K	80+	24/12	A
S11482	36PS30/LED/850/120V/DIM/E26	36W	4500	5000K	80+	24/12	A
S11483	36PS30/LED/827/120V/DIM/E39	36W	4500	2700K	80+	24/12	A
S11485	36PS30/LED/850/120V/DIM/E39	36W	4500	5000K	80+	24/12	A




SIZE LEGEND	LENGTH (MOL)	DIAMETER (MOD)
A	7.32"	3.74"

[illegible]



20 horizontal lines for writing.





Scan For Digital Catalog

To learn more about SATCO|NUVO, visit www.satco.com or contact 1-800-437-2826



Like us on Facebook



Connect with us on LinkedIn



Follow us on Instagram

National Toll-Free:

1.800.43.SATCO (1.800.437.2826)

**Corporate Offices &
Distribution Center:**

NEW YORK 110 Heartland Blvd., Brentwood, NY 11717 | 800.437.2826 | 631.243.2022 | Fax 631.243.2027

Distribution Centers:

FLORIDA 1694 NW 215th St. Miami Gardens, FL 33056 | Tel. 305.624.2044 FAX 305.623.0286

CALIFORNIA 31288 San Benito St. Hayward, CA 94544 | Tel. 510.487.4822 FAX 510.487.8955

WASHINGTON 4710 116th St. S.W., Mukilteo, WA 98275 | Tel. 425.789.3300 FAX 425.789.3310

TEXAS 2000 Valwood Parkway, Farmers Branch, TX 75234 | Tel. 972.247.2437 FAX 972.247.5408

PUERTO RICO Campeche St. 23, Julio N. Matos Industrial Park, Carolina, PR 00984 | Tel. 787.757.3510 FAX 787.757.3540

Product specifications and availability are subject to change without notice.

Please visit us online at www.satco.com for our full product line and ordering details, or consult factory for additional information