



4 CCT SELECTABLE

TYPE A BALLAST COMPATIBLE

Fa8 BASE

PET COATED GLASS

SUGGESTED APPLICATIONS

Offices
Retail
Parking Garages
Warehouses

LED T12 LAMPS

BALLAST COMPATIBLE | CCT SELECTABLE



S11657-4' Length



S11658-5' Length



S11659-6' Length

Upgrade existing T12 fluorescent lamps with SATCO's versatile LED tubes. These Type A ballast-compatible LED T12 Tubes offer four CCT-selectable options, allowing for flexible color temperature selection at installation. Available in 4', 5', and 6' lengths with an Fa8 base, these lamps feature durable glass tube construction and are damp location rated. They are also dimmable down to 10% when used with compatible dimming ballasts, making them a flexible solution for commercial, retail, office, and general lighting applications.



GENERAL SPECIFICATIONS

Efficacy: Up to 166 LPW

CRI: 80+

CCT Selectable: 3500/4000/5000/6500K

Wiring: Double-Ended

Dimmable: With Compatible Ballast Down to 10%

Beam Angle: 240°

Type A: Ballast Compatible

Location Rating: Damp

Ambient Operating Temperature: -4°F to +113°F (-20°C to +45°C)

Construction: Glass Tube with Plastic End Caps

Base: Fa8 Single Pin

Functional Life: 36,000 Hours

Warranty: 3 Year



ITEM SPECIFICATIONS / ORDER INFO

Item	Description	Length	Lumens	Wattage	Fluorescent Replacement	Case QTY
S11657	21T12L48/8CCT4/FA8/A/CF/ND/U	4'	3500	21W	F48T12 (39W)	10
S11658	28T12L60/8CCT4/FA8/A/CF/ND/U	5'	4100	28W	F60T12 (50W)	10
S11659	35T12L72/8CCT4/FA8/A/CF/ND/U	6'	5000	35W	F72T12 (55W)	10

NOMENCLATURE


21T12L48/8CCT4/FA8/A/CF/ND/U

1 2 3 4 5 6 7 8 9 10 11


- 1 - Wattage
- 2 - Lamp Type
- 3 - LED
- 4 - Nominal Length
- 5 - CRI (80)
- 6 - 4 CCT Selectable
- 7 - Base Type (Fa8)
- 8 - UL Type A: (Ballast Compatible)
- 9 - PET Coated Glass
- 10 - Non-Dimmable
- 11 - Universal Voltage (120-277V)

DIMENSIONS / WEIGHTS

Item	Length (A)	Width (B)	Weight
S11657	46.02"	1.40"	0.75 Lbs.
S11658	58.00"	1.40"	0.93 Lbs.
S11659	70.00"	1.40"	1.10 Lbs.




FEATURES



CCT Selectable Switch



Fa8 Base



PET Coated Glass

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Meets requirements of ICES-005 issue 5: Class A for use in commercial applications

Fixture may not be compatible with all dimmers. See satco.com for details.

Specifications are subject to change without prior notice.

Replacement wattage shown depends on application and fixture.

WARNING: Some products included in this specification sheet may be subject to the warning requirements of California's Proposition 65. Please refer to your product packaging for more information.

Visit satco.com/service/warranty for complete warranty details.